


Industrial high bay LED luminaires

PRIMARY APPLICATIONS

- IHB LED luminaires are the perfect replacement for 250W-1,500W HID and 4-10 lamp T5HO fluorescent high bay fixtures. Designed for locations requiring continuous and consistent light levels, requiring frequent on-and-off of lights and that is difficult to relamp or causes production to be stopped during the lamp maintenance process.

LUMINAIRE MODELS

| Model | Equivalent HID luminaire | Energy savings |
|--------|----------------------------------|----------------|
| IHB16L | 250-500W HID or 4 lamp T5HO | Up to 72% |
| IHB24L | 400-750W HID or 4-6 lamp T5HO | |
| IHB32L | 500-1,000W HID or 6-8 lamp T5HO | |
| IHB48L | 750-1,500W HID or 8-10 lamp T5HO | |
| IHB64L | 1,000-1,500W HID or 10 lamp T5HO | |



Perfect replacement for 400-1500 watt HID or 4-10 lamp T5HO fixtures

DESIGN FEATURES

- A. Increased efficiency** - Up to 117 lumens per watt.
- B. Multiple mounting options** - Available with pendant, aircraft cable or jack chain mounting.
- C. Aluminum heat sinks for superior thermal management.**
- D. Multiple lens options** - Tempered and clear glass standard, diffused glass and clear or diffused polycarbonate options available.
- E. Optional occupancy sensor kit available.**

CERTIFICATION AND COMPLIANCES

- UL1598; UL8750
- cULus
- Damp location
- DesignLights Consortium® approved for select models

ELECTRICAL RATINGS

- Volts: 100-277 VAC / 127-250 VDC, 347-480 VAC
- Input power: 145W, 216W, 289W, 436W, 582W

OPTIONS AND ACCESSORIES

- Occupancy sensor kits
- Diffused or clear lens (glass or polycarbonate)
- Lens guard
- Open ended and closed dust cover kits
- Dimmable driver
- Wide or aisle optic
- Pendant, aircraft cable or jack chain mounting



* Refer to www.designlights.org Qualified Products List under family models for full listing details. Not all models are approved for all application categories.